## Why pack it when you can...



Thank you for purchasing the best looking rack in the motorcycle industry. Your new rack is constructed of 6061 billet aluminum and then anodized to give you a high quality and good-looking rack for years of backpack free riding enjoyment.



Manufactured by: Pro Moto Billet 11461 Lone Star Rd Nampa ID 83651

208-466-4762

## Instructions: KTM 98-03 2 STROKE\*00-04 RACING 4 STROKE (PMB-01-3203)

## We recommend using a removable thread-locking agent on all bolts.

- 1. Remove stock rear fender bolts and seat bolts; leave the fender washers in place in the plastic.
- 2. We recommend using a thread-locking agent on all bolts if vibration is a problem.
- 3. Loosely install the two L-shaped brackets under the fender using two 6x30mm flat head bolts. Make sure the stock fender washers are in place.

**NOTE:** If you have a model without the black fender extension, install the 6x16x5 spacers between the L-shaped bracket and the stock fender washer. (If you have the equipment, you could trim .2" off of each of the end of the L-shaped brackets and eliminate the spacers.

- 4. Install the rack side supports to the L-shaped brackets using four 6x25mm flat head bolts.
- 5. Loosely install the two 6x50mm flat head bolts into the front holes on the rack side supports, and into the seat mounting holes, with the one of the 6x16x22 stepped spacers between each of the rack side supports and the side panels.
- 6. Install the rack top to the rack side supports using four 6x16mm flat head bolts.
- 7. Tighten the four bolts holding the rack side supports to the L-shaped brackets.
- 8. Tighten the rear fender bolts that are holding the L-shaped brackets to the bike.
- 9. Tighten the seat mounting bolts.
- 10. Tighten the rack top to rack side support bolts.
- 11. Make sure that all bolts are tight.

<u>CAUTION:</u> As with all racks on dirt bikes, they should not have excess amounts of weight put on them. Excess weight can damage the rear sub-frame of the motorcycle.

## Parts List:

1-Top

2-Sides

2-Brackets

2-6x30 FH

4-6x25 FH

2-6x50 FH

4-6x16 FH

2-6x16x5 Spacer

2-6x16x22 Stepped Spacer