



11461 Lone Star Rd Nampa ID 83651 · 208-466-4762

**Instructions: KAWASAKI 03-13 KX/KXF/KLXR\*\*\*SUZUKI 04-05 RMZ250  
(PMB-01-9017B)**

This disc guard comes with a new wheel spacer with an integrated mount to reinforce the stock mounting tabs on the brake carrier. To install this disc guard, please read the instructions carefully.

1. Remove the rear axle cotter pin, nut and axle.
2. Remove rear wheel.
3. Remove the right side rear wheel spacer from the hub.
4. Remove the dust cover from the rear wheel spacer.
5. Install the dust cover on the new wheel spacer with integrated mount.
6. Install the wheel spacer with integrated mount into the hub.
7. Re-install the rear wheel. You will have to rotate the wheel spacer with integrated mount so that it is pointing down towards the ground.
8. Re-install the rear axle and nut (do not tighten it all of the way!).
9. After the rear axle is installed, rotate the wheel spacer with integrated mount up into the horizontal position and install the disc guard using the four 6x16 socket head bolts that are provided.
10. Now would be a good time to adjust your chain if necessary.
11. Tighten the rear axle nut and install the cotter pin.

**REMEMBER:** When removing the rear wheel assembly you will have to remove all four bolts from the disc guard and rotate the wheel spacer with integrated mount towards the ground in order to get the rear wheel off of the bike.

**Parts List:**

**1-Fin  
1-Mount  
4-6x16 SH**

Check out our Spark Arrestor Endcaps, Billet Cargo Racks, Shark Fins and other billet accessories at...

